



## Features

### Standard Features

- SONY Super HAD Sensor
- Resolution 700TVL
- Robust Casing
- IR Function
- Multiple Auto Functions (exposure, gain, focus, etc)
- Day / Night function

### Enhanced Features

- IP66 Rated
- Privacy Masking
- On-screen-display
- 50m IR distance

### Software

- ZKIVision Software

# Dot 2 SIR285

CCTV  
Analogue Range



### Related Products



DVR



Software

### Alternative Products



Bullet



Dot 1 (30m IR)



Dot 1 (Face Detection)



Dot 4 (80m IR)

## Specifications

• Image Sensor:	1/3" SONY Super HAD CCD
• Pixels:	PAL: 1020H X 596V NTSC: 1020H X 508V
• Horizontal Resolution:	700TVL
• Min Illumination:	0.001 Lux / F12 (LED on)
• System:	PAL / NTSC
• Lens:	8mm
• IR Distance:	50m
• SNR (Signal Noise Ratio):	≥48db (AGC OFF)
• Shutter Speed:	1 / 50 (1 / 60) ~ 1 / 120,000s
• Gamma Correction:	0.45
• White Balance:	Auto
• Backlight Compensation:	Auto
• Sync Mode:	Internal synchronization
• Video Out Rate:	1.0Vp-p at 75Ω, BNC
• Power:	DC12V
• Working Temperature:	-10°C ~ 50°C
• Storage Temperature:	-20°C ~ 60°C
• Dimensions:	157 (L) X 105 (W) X 72.5 (H)mm
• Gross Weight:	780g
• Dimensions of packaging:	232 X 143 X 122mm

## Dimensions

